

UCS30-1H12V (107200350101)

Product Feature

- A channel constant voltage output
- Applicable to indoor LED lights
- Small size, high efficiency, high reliability and long life time
- -25°C~+50°C, working temp
- Protections: overload, overvoltage, short circuit self-recovery protection
- Compliance with CE and ROHS
- 100% Full load aging test
- The warranty period is 5 Years





Application



Technical Parameters

Model	UCS30-1H12V	
Input	Efficiency	83%@220VAC, Full load
	Voltage	220VAC-240VAC
	Frequency	50-60Hz
	Power Factor	>0.95
	Current	0.2Amax@220VAC
	THD	<15% (at 220V, 50Hz, full load)
	Inrush Current	Cold start <60A @200VAC(full load)
Output	Current/Voltage/Power	2.5A/12VDC/30W
	Channel	1
	Voltage Tolerance	±5%
Protection	Short Circuit	Hiccup, remove fault and recover
	Over Voltage	Hiccup, remove fault and recover
	Over Current	Hiccup, remove fault and recover
Others	Working Temp.	-20°C~+50°C
	Storage Temp.; Humidity	-40°C~85°C, 20-90%RH
	Tc	90°C
	Material	PC
	IP Rating	IP20
	Lifetime	50,000h@ta:40°C
	Warranty Condition	5 Years
	Switch Cycle	>25,000 times
	Packing Size	Net weight: 115g±5%/PCS; 50PCS/Carton; 6.25kg±5%/Carton; Carton Size: 365*228*199mm(L*W*H)
Dimension	250*30*17mm(L*W*H)	


Dimension(mm)



Wiring Diagram



Derating Curve




Nameplate

L (Brown) (棕色) N (Blue) (蓝色)		LED Constant Voltage Power Supply Model:UCS30-1H12V Wire PRI: Uin: 220V-240V~ 50/60 Hz λ>0.95 Pin: 37.5W Iin:0.19Amax SEC: Prated: 30W Irated: 2.5A Urated: 12V Uout:13V PF: 0.95 ta:-20...+50°C tc:85°C For LED modules only	LED控制装置 	107200350101 5mm wire preparation 预留5mm 	OUTPUT + -
		● tc		1.5°	

Cautions

- 1.The product shall be installed and serviced by a qualified person.
- 2.This product is non-waterproof. Please avoid the sun and rain. When installed outdoors please ensure it is mounted in a water proof enclosure.
- 3.Good heat dissipation will prolong the working life of the controller. Please ensure good ventilation.
- 4.Please check if the output voltage and current of any LED power supplies used comply with the requirement of the product.
- 5.Please ensure that adequate sized cable is used from the controller to the LED lights to carry the current. Please also ensure that the cable is secured tightly in the connector.
- 6.For safety consideration, PVC or rubber cord of 0.75-1.5mm² is recommended for input and output terminal(s) .Flat power cord is not suitable. Ensure all wire connections and polarities are correct before applying power to avoid any damages to the LED lights.
- 7.The power supply should be strictly and reliably grounded to prevent electric shock.
- 8.If a fault occurs please return the product to your supplier. Do not attempt to fix this product by yourself.



※ The contents of this manual are updated without prior notice. If the function of the product you are using is inconsistent with the instructions, the function of the product shall prevail. Please contact us if you have any questions.

UCS30-1H12V (107200350101)

产品特点

- 单通道恒压输出
- 适用于LED室内灯具
- 小体积、高效率、高可靠、长寿命；
- 在-20°C~+50°C工作正常；
- 保护种类：过载、过压、短路自恢复保护；
- 符合CE认证，符合RoHS环保标准；
- 100%满载老化测试；
- 保固期5年；




应用




技术参数

型号	UCS30-1H12V	
输入	效率	83%@220VAC, 满载
	电压	220VAC-240VAC
	频率	50-60Hz
	功率因数	>0.95
	电流	0.2Amax@220VAC, 满载
	THD	<15%(at 220V, 50Hz, 满载)
	浪涌电流	冷启动 <60A @200VAC(满载)
输出	电流/电压/功率	2.5A/12VDC/30W
	通道	1
	电压公差	±5%
保护	短路	打嗝，移除故障后自恢复
	过压	打嗝，移除故障后自恢复
	过流	打嗝，移除故障后自恢复
其它	工作温度	-20°C-50°C
	储存温度、湿度	-40°C-85°C, 20-90%RH
	Tc	90°C
	材质	PC
	防水等级	IP20
	寿命	50,000h@ta:40°C
	质保	5年
	开关周期	>25,000次
	包装重量	净重: 115g±5%/个; 50个/箱; 6.25kg±5%/箱; 外箱尺寸: 365*228*199mm[长*宽*高]
	产品尺寸	250*30*17mm[长*宽*高]


产品尺寸(mm)



应用接线图



降额曲线




铭牌

<p>L (Brown) (棕色) 输入</p> <p>N (Blue) (蓝色) 输入</p>	<p>LED Constant Voltage Power Supply LED控制装置</p> <p>Model:UCS30-1H12V Wire</p> <p>PR: Uin: 220V-240V~ 50/60 Hz λ>0.95 Pin: 37.5W Iin:0.19Amax</p> <p>SEC: Prated: 30W Irated: 2.5A Urated: 12V Uout:13V</p> <p>PF: 0.95 ta:-20...+50°C tc:85°C ● tc</p> <p>For LED modules only</p>		<p>107200350101</p> <p>5mm wire preparation 预留5mm</p> <p>1.5°</p>	<p>OUTPUT +</p> <p>OUTPUT -</p>
	<p>IP20 CE SELV</p>			

注意事项

- 1、本产品请由具有专业资格的人员进行调试安装。
- 2、本产品不能防水，需避免日晒雨淋，如安装在户外，请用防水箱。
- 3、良好的散热条件会延长产品的使用寿命，请把产品安装在通风良好的环境。
- 4、请检查使用的LED电源输出电压电流，是否符合产品要求。
- 5、使用的电线直径大小必须能够足够负载连接的LED灯具，并确保接线牢固，以免电线过热或接触不良触发事故。
- 6、通电调试前，应确保所有接线正确，以避免因接线错误而导致灯具损坏。
- 7、安装在金属表面，电源应严格可靠接地，以防漏电触电。
- 8、如果发生故障，请勿私自维修；如有疑问，请联系供应商。



※ 本说明书内容如有更新，恕不另行通知。若您使用的产品功能与说明书不一致时，请以产品为准。如有疑问请与我们联系。