

Intelligent LED Driver (Constant Voltage)

- Adopt SAMSUNG/COVESTRO V0 flame resistant polycarbonate protective housings with small size and light weight.
- Bluetooth 5.0 SIG Mesh with high networking capability are reliable and stable.
- With soft-on and fade-in dimming function enhancing visual comfort.
- Support control iOS or Android devices through Bluetooth connection.
- 0-100% dimming range, down to 0.1%.
- Energy-efficient driver: Efficiency 93%, PF>0.98, THD<6%.
- Comply with the EU's ErP Directive, standby power consumption<0.5W.
- Innovative thermal management technology protects the power life intelligently.
- Overheat, overvoltage, overload, short circuit protection and automatic recovery.
- The design of removable end housing is convenient to adjust the length of driver.
- Suitable for indoor light applications of I / II / III type.
- Up to 50,000-hour life time.
- 5-year warranty (Rubycon capacitor).



Flicker Free
IEEE 1789

Dimmable:
0.1%-100%



The certification icon represents undergoing certification applications only, and final certification qualification subject to actual product.




Technical Specs

Model	LM-150-24-G1B2		LM-150-12-G1B2
OUTPUT	Output Voltage	24Vdc	12Vdc
	Output Voltage Range	24Vdc ± 0.5Vdc	12Vdc ± 0.5Vdc
	Output Current	Max. 6.25A	Max. 12.5A
	Output Power	Max. 150W	
	Output Power Range	0~150W	
	Strobe Level	High frequency exemption level	
	Dimming Range	0~100%, down to 0.1%	
	Overload Power Limitation	≥102%	
	Ripple	Switch ripple<200mV, noise≤500mV	Switch ripple<200mV, noise≤800mV
	PWM frequency	3600Hz	
INPUT	Dimming Interface	Bluetooth 5.0 SIG Mesh	
	Input Voltage	220-240Vac, 200-280Vdc	
	Frequency	50/60Hz	
	Input Current	<0.75A/230Vac	
	Power Factor	PF>0.98/230Vac (at full load)	
	THD	THD<6%@230Vac (at full load)	
	Efficiency (typ.)	93%	92%
	Standby Power Loss	<0.5W	
	Inrush Current	Cold start 45A[Test twidth=500us tested under 50% lpeak)/230Vac	
	Anti Surge	L-N: 2KV	
ENVIRONMENT	Leakage Current	Max. 0.5mA	
	Working Temperature	ta: -20 ~ 50°C tc: 85°C	
	Working Humidity	20 ~ 95%RH, non-condensing	
	Storage Temperature,Humidity	-40 ~ 80°C, 10-95%RH	
	Temperature Coefficient	±0.03%/°C(0-50°C)	
PROTECTION	Vibration	10-500Hz, 2G 12min/1cycle, 72 min for X, Y and Z axes respectively	
	Overheat Protection	Intelligently adjust or turn off the output current if the PCB temperature ≥110°C, and recover automatically	
	Overload Protection	Shut down the output when current load≥102%, and recover automatically	
	Short Circuit Protection	Enter hiccup mode if short circuit occurs, and recover automatically	
	Overvoltage Protection	Shut down the output when non-load voltage≥28V, and recover automatically	Shut down the output when non-load voltage≥16V, and recover automatically
SAFETY & EMC	Withstand Voltage	I/P-O/P: 3750Vac	
	Isolation Resistance	I/P-O/P: 100MQ/500VDC/25°C/70%RH	
	Safety Standards	CCC China	GB19510.1, GB19510.14
		TUV Germany	EN61347-1, EN61347-2-13, EN62493
		CB CB member states	IEC61347-1, IEC61347-2-13
		CE European Union	EN61347-1, EN61347-2-13, EN62384, EN61547
		KC Korea	KC61347-1, KC61347-2-13
		EAC Russia	IEC61347-1, IEC61347-2-13
		RCM Australia	AS 61347-1, AS 61347-2-13
	EMC Emission	EMEC Europe	EN61347-1, EN61347-2-13, EN62384
		UKCA Britain	BS EN 61347-2-13:2014+A1:2017, BS EN 61347-1:2015+A1:2021
		CCC China	GB/T17743, GB17625.1
		CE European Union	EN55015, EN61000-3-2, EN61000-3-3, EN61547
		KC Korea	KS C 9815, KS C 9547
	EMC Immunity	EAC Russia	IEC62493, IEC61547, EH55015
		RCM Australia	EN55015, EN61000-3-2, EN61000-3-3, EN61547
		UKCA Britain	BS EN IEC 55015:2019/A11:2020, BS EN 61547:2009, BS EN IEC 61000-3-2:2019, BS EN 61000-3-3:2013/A1:2019
		EMC Immunity	EN61000-4-2,3,4,5,6,8,11, EN61547
		Strobe Test Standard	IEEE 1789
OTHERS	Gross weight(G.W)	430g±10g	
	Dimensions	352×43×30mm(L×W×H)	


The driver is suitable for connecting resistor current-limiting LED fixture (e.g. LED strip). The inrush current will be dozens of times increased if connecting built-in constant current IC current-limiting LED fixtures, the driver will activate the overloaded protection (hiccup flickering). When you order, please remark controlling the constant current LED fixture (e.g. MR16 lamp, underground light, LED wall washer, constant current LED strip, etc.), so that we can prepare them with special procedures.

Product Size


Unit: mm



Wiring Diagram





Protective Housing Application Diagram





Open the protective housing and push the side housing outwards to pry up the wire fixing board with a screwdriver . Then connect to electrical wires as wiring diagram shows. Press down the wire fixing board to fix the the electrical wires, finally close the protective housing.

Press down the back side of the protective housing and move it from side to side to remove it.



Installation Precautions





Please do not stack the products. The distance between two products should be $\geq 15\text{cm}$ so as not to affect heat dissipation and the lifespan of the products.



Please do not place the products on the floor. The distance between the product and the floor should be $\geq 100\text{cm}$ so as to avoid signal interference.











Please do not place the products near a large area of metal objects (such as metal stud ceilings). The distance between the product and the metal object should be $\geq 15\text{cm}$ so as to avoid signal interference.



Please do not install the products on beams or near the corners. The distance between the product and the beam or the corner should be $\geq 15\text{cm}$ so as to avoid signal interference.

Relationship Diagrams





LM-150-12-G1B2


Flicker Test Table

IEEE 1789


Limit Value of Modulation in Low Risk Areas	
Waveform frequency of optical output	Limit value [%]
$f \leq 8\text{Hz}$	0.2
$8\text{Hz} < f \leq 90\text{Hz}$	$0.025 \times f$
$90\text{Hz} < f \leq 1250\text{Hz}$	$0.08 \times f$
$f > 1250\text{Hz}$	Exemption assessment

Limit Value of Modulation in No Effect Areas	
Waveform frequency of optical output	Limit value [%]
$f \leq 10\text{Hz}$	0.1
$10\text{Hz} < f \leq 90\text{Hz}$	$0.01 \times f$
$90\text{Hz} < f \leq 3125\text{Hz}$	$(0.08/2.5) \times f$
$f > 3125\text{Hz}$	Exemption assessment (High frequency exemption)

- Brightness**
- ▲ 0.1 %
 - ◆ 1 %
 - ▲ 5 %
 - ◆ 10 %
 - 20 %
 - ▲ 30 %
 - 40 %
 - ★ 50 %
 - 60 %
 - 70 %
 - 80 %
 - ★ 90 %
 - ◆ 100 %




System Diagram




Recommend Applications


1. Achieve fast dimming control.



2. Both App and remote can control the driver after connecting the remote to the driver with App.



3. Both App and Super Panel 6S can control the driver simultaneously after connecting the Super Panel 6S to the driver with App. By connecting the Super Panel to network, you are allowed to control the driver, cloud scenes and automation remotely with App.



4.More applications of intelligent control are waiting for you to set up.

App Operating Instructions

1. Register an account

The App is available on iOS or Android devices. Scan the QR code below with your mobile phone and follow the prompts to complete the App installation. Open the App to log in or register an account.



Scan and download the APP


2. Pairing instructions

Open the APP and create a home if you are a new user. Click “+” icon in the upper right corner and access the “Add Device” list, then follow the prompts to add the device. Pick “Smart lighting-DIM light” from the list and follow the prompts to power on the device firstly. Make sure the device is not connected to the network. Then click “Bluetooth Search” and follow the prompts to add the device.




3. Control interface settings

After pairing up your device, go to the control interface. You'll be able to achieve your desired lighting effects by changing brightness. Click "Theme" and you'll easily switch to multiple theme lighting effects with one tap. Click "Mode" and the App provides you editable advanced modes. Customize dynamic modes to put you into a more colorful life.




4. Light groups

Users are able to combine the same type of light fixtures into a group to control them simultaneously. Once you create the group, you can set the dim level more easily. Pick "Group-DIM light group" from the list. Follow the prompts to rename the group and click "Next" to pick the lights you are going to group together and click "Save".




5. Advanced functions

This driver can be linked up with gateway function devices (such as Super Panel 6S) to achieve the advanced functions from local scenes and cloud scenes to automation.



Reset The Device (Reset to factory defaults)


Make sure the driver is well-connected to a lamp and the lamp is on, turn it off with the switch and after 15s turn it on. After 2s, turn it off again. Repeat the same operation 6 times. When the lamp flashes 5 times, reset the device to factory defaults successfully.



Packaging Specifications

Model	LM-150-24-G1B2 / LM-150-12-G1B2
Carton Dimensions	370×340×93mm(L×W×H)
Quantity	10PCS/Layer; 2Layer/Carton; 20PCS/Carton
Weight	0.43kg/PC; 9.4kg±5%/Carton

Packaging Image



Inner Packaging Box



Carton Packaging

Transportation and Storage

1. Transportation

Products can be shipped via vehicles, boats and planes.

During transportation, products should be protected from rain and sun. Please avoid severe shock and vibration during the loading and unloading process.

2. Storage

The storage conditions should comply with the Class I Environmental Standards. The products that have been stored for more than six months are recommended to be re-inspected and can be used only after they have been qualified.

FAQs

1. What should I do if I fail to add the device?

- 1.1 Please make sure the device is powered on normally and is in the activated mode.
- 1.2 Please make sure the device hasn't been added by any other account. If it did, please reset to factory defaults manually.
- 1.3 The recommended distance between the mobile phone and the device is no more than 20 meters.
- 1.4 If the device has been forced to delete, please reset to factory defaults manually and then add the device again.

2. What should I do if the device disconnects from the network?

- 2.1 Please make sure the device is powered on normally.
- 2.2 Please make sure the router works with network available.
- 2.3 If you control the device remotely, please make sure your phone network works normally.

3. How to control remotely and set cloud scenes?

Remote control and cloud scenes can be achieved only by working with LTECH Super Panel.

4. How to share control of your home devices?

Please go to "Me" - "Home Management" and access the home you want to share. Click "Add Member" and follow the prompts to add members into your home.

Attentions

- This product must be installed and adjusted by a qualified professional.
- This product is non-waterproof (special models excepted). Please avoid the sun and rain. When installed outdoors, please ensure it is mounted in a water proof enclosure.
- Good heat dissipation will extend the life of the product. Please install the product in an environment with good ventilation.
- When you install this product, please avoid being near a large area of metal objects or stacking them to prevent signal interference.
- Please keep the product away from an intense magnetic field, a high pressure area or a place where lightning is easy to occur.
- Please check whether the working voltage used complies with the parameter requirements of the product.
- Before you power on the product, please make sure all the wiring is correct in case of incorrect connection that may cause a short circuit and damage the components, or trigger a accident.
- If a fault occurs, please do not attempt to fix the product by yourself. If you have any question, please contact the supplier.

* This manual is subject to changes without further notice. Product functions depend on the goods. Please feel free to contact our official distributors if you have any question.

Warranty Agreement

- Warranty periods from the date of delivery: 5 years.
- Free repair or replacement services for quality problems are provided within warranty periods.

Warranty exclusions below:

- Beyond warranty periods.
- Any artificial damage caused by high voltage, overload, or improper operations.
- Products with severe physical damage.
- Damage caused by natural disasters and force majeure.
- Warranty labels and barcodes have been damaged.
- No warranty signed by LTECH.

1. Repair or replacement provided is the only remedy for customers. LTECH is not liable for any incidental or consequential damage unless it is within the law.
2. LTECH has the right to amend or adjust the terms of this warranty, and release in written form shall prevail.

Update Log

Version	Updated Time	Update Content	Updated by
A0	2021.04.09	Original version	Liu Weili
A1	2021.06.05	Update TUV certification icon	Liu Weili
A2	2021.12.10	Update product silk screen	Liu Weili
A3	2023.03.15	The warranty period is changed to 5 years	Liu Weili

LED智能调光驱动器(恒压型)

- 体积小、重量轻；采用SAMSUNG/COVESTRO PC V0阻燃保护壳
- 免螺丝压线翻盖设计，可拆卸端盖，按需调节壳体长度
- Bluetooth 5.0 SIG Mesh通信协议，组网能力强，可靠稳定
- 支持iOS和安卓智能设备蓝牙直连控制
- 带软启动渐亮功能，让人眼视觉更舒适
- 调光范围：0-100%，LED从0.1%开始调光
- 高效能电源：效率93%，PF>0.98、THD<6%
- 符合欧盟能效ERP指令，待机功耗<0.5W
- 创新的热管理技术，智能保护电源寿命
- 过温、过压、过载、短路保护，可自动恢复
- 适合室内I、II、III类灯具应用
- 高达50,000小时的额定寿命
- 5年保修期（采用红宝石电容）



无频闪

IEEE 1789

高频豁免考核级别

Dimmable:

0.1%-100%



认证图标仅代表产品正在进行这一系列的认证申请，认证资质以产品实物为准。




技术参数

型号	LM-150-24-G1B2	LM-150-12-G1B2
输出	输出电压	24Vdc
	输出电压范围	24Vdc ± 0.5Vdc
	输出电流	Max. 6.25A
	输出功率	Max. 150W
	输出功率范围	0~150W
	频闪级别	高频豁免考核级别
	调光范围	0~100%，调光深度：0.1%
	过功率限制	≥102%
	纹波与噪声	开关纹波≤200mV，噪声≤500mV
	PWM调光频率	3600Hz
输入	调光接口	Bluetooth 5.0 SIG Mesh
	输入电压	220-240Vac 200-280Vdc
	频率范围	50/60Hz
	输入电流	Max. 0.75A/230Vac
	功率因数	PF>0.98/230Vac (满载)
	谐波THD	230Vac@THD<6% (满载)
	效率(Typ.)	93% 92%
	待机功耗	<0.5W
	浪涌电流	冷启动45A (在50%Ipeak下测试twidth=500us)/230Vac
	抗浪涌	L-N: 2KV
环境	漏电流	Max. 0.5mA
	工作温度	ta: -20 ~ 50°C tc: 85°C
	工作湿度	20 ~ 95%RH, 无冷凝
	储存温度/湿度	-40 ~ 80°C, 10~95%RH
	温度系数	±0.03%/°C(0-50°C)
保护	耐振动	10-500HZ, 2G 12分钟/周期, X, Y, Z轴各72分钟
	过温保护	根据PCB温度超标情况(≥110°C)，智能调节电流输出或关闭，可自动恢复
	过载保护	负载电流≥102%，关闭输出，可自动恢复
	短路保护	输出线路短路进入打嗝模式，可自动恢复
安规和电磁规格	过压保护	空载电压≥28V, 关闭输出，可自动恢复 空载电压≥16V, 关闭输出，可自动恢复
	耐压	输入对输出: 3750Vac
	绝缘阻抗	输入对输出: 100MΩ/500VDC/25°C/70%RH
	安全规范	CCC 中国 GB19510.1, GB19510.14
		TUV 德国 EN61347-1, EN61347-2-13, EN62493
		CB CB成员国 IEC61347-1, IEC61347-2-13
		CE 欧盟 EN61347-1, EN61347-2-13, EN62384
		KC 韩国 KC61347-1, KC61347-2-13
		EAC 俄罗斯 IEC61347-1, IEC61347-2-13
		RCM 澳洲 AS 61347-1, AS 61347-2-13
		ENEC 欧洲 EN61347-1, EN61347-2-13, EN62384
	UKCA 英国 BS EN 61347-2-13:2014+A1:2017, BS EN 61347-1:2015+A1:2021	
	电磁兼容发射	CCC 中国 GB/T17743, GB17625.1
		CE 欧盟 EN55015, EN61000-3-2, EN61000-3-3, EN61547
		KC 韩国 KS C 9815, KS C 9547
		EAC 俄罗斯 IEC62493, IEC61547, EH55015
		RCM 澳洲 EN55015, EN61000-3-2, EN61000-3-3, EN61547
	UKCA 英国 BS EN IEC 55015:2019/A11:2020, BS EN 61547:2009, BS EN IEC 61000-3-2:2019, BS EN 61000-3-3:2013/A1:2019	
	电磁兼容抗扰度	EN61000-4-2,3,4,5,6,8,11, EN61547
	频闪测试标准	IEEE 1789
其他	产品重量	430g±10g
	产品尺寸	352×43×30mm(L×W×H)

本款驱动器适合连接电阻限流的LED灯具(如LED灯条)。如果连接内置恒流IC限流的灯具，会产生几十倍的瞬间浪涌电流，导致驱动器会执行过载保护(打嗝频闪)。下单时这类内置恒流IC限流的灯具需要注明(如MR16灯杯、地埋灯、洗墙灯、恒流硬灯条等)，以便烧写特殊程序。


尺寸图

单位: mm



连接应用图

无线连接方式



保护盖应用图

压线安装





保护盖拆卸





打开保护盖, 向外推压侧板并用螺丝批向上撬起将压线板拆下, 按照接线图接线后向下按压线板固定住线, 合上保护盖即可。

在外壳底部往下按压并左右掰动, 即可将保护盖拆下。



安装注意事项





请勿将产品堆叠摆放，产品与产品间隔距离应 $\geq 15\text{cm}$ ，避免影响产品散热和使用寿命。



请勿将产品放置地面，与地面间隔距离应 $\geq 100\text{cm}$ ，以免信号干扰影响使用。




请勿将产品大面积接触金属物体(如：龙骨架)，间隔距离应 $\geq 15\text{cm}$ ，以免信号干扰影响使用。




请勿将产品安装在横梁、墙角等位置，间隔距离应 $\geq 15\text{cm}$ ，以免信号干扰影响使用。

关系图表


效率与负载关系图




功率因素特征图







THD与负载关系图



过载曲线



LM-150-24-G1B2




LM-150-12-G1B2


频闪测试表

IEEE 1789

低风险区域 (Low Risk) 的波动深度 (Modulation) 限值	
光输出波形频率 f	限值 (%)
$f \leq 8\text{Hz}$	0.2
$8\text{Hz} < f \leq 90\text{Hz}$	$0.025 \times f$
$90\text{Hz} < f \leq 1250\text{Hz}$	$0.08 \times f$
$f > 1250\text{Hz}$	免除考核
无风险区域 (No Effect) 的波动深度 (Modulation) 限值	
光输出波形频率 f	限值 (%)
$f \leq 10\text{Hz}$	0.1
$10\text{Hz} < f \leq 90\text{Hz}$	$0.01 \times f$
$90\text{Hz} < f \leq 3125\text{Hz}$	$(0.08/2.5) \times f$
$f > 3125\text{Hz}$	免除考核 (高频豁免)




系统图



推荐应用控制方式


1、快速实现本地调光。



2、通过APP设置遥控关联驱动后，可实现APP与遥控两种控制方式控制驱动。



3、通过APP设置面板关联驱动，可实现APP与面板同时控制。并能够通过面板联网，可实现APP远程控制驱动，云场景，自动化联动功能。



4、.....智能控制，更多应用搭配等您来设置。

APP操作说明

1. 账号注册

APP兼容iOS和Android系统，通过手机扫描下方二维码，按提示完成APP安装，安装后即可进行登录/注册操作。



2. 配对操作

新用户创建家庭后，点击右上角“+”进入添加设备列表，先将驱动器按照提示添加完成后，在添加设备列表选择“智能照明-调光灯”后，按照界面提示，先将设备接通电源，确保设备处于未入网状态。然后点击“蓝牙搜索”后，按照提示完成添加设备。



3. 控制界面设置

配对完成后，进入控制界面，可以通过调节亮度达到想要的灯光效果。点击主题，进入主题界面，可一键切换多种主题灯光效果。点击模式，具有可编辑的高级模式。自定义动态模式，让您的生活更加丰富多彩。



4. 灯具群组

同类型的灯具可以组成群组，用户可以对群组进行调光等操作，操作更便利。在添加设备列表中选择“群组—调光灯组”，按照界面提示编辑灯组名称后，点击“下一步”，勾选您要组成群组的设备，保存即可。




5. 高级功能

本产品可以通过与具有网关功能的设备联动，如超级面板6S。可实现本地场景、云场景、自动化等高级功能。



重置设备 (恢复出厂设置)


确保驱动已接灯具且处于常亮状态，使用开关让驱动连续断电6次（每次断电时间15秒，通电2秒），第六次通电2秒后，灯具闪烁5次，即表示驱动已恢复到出厂设置状态。



包装规格

型号	LM-150-24-G1B2 / LM-150-12-G1B2
包装箱尺寸	370×340×93mm(L×W×H)
数量	10PCS/层；2层/箱；20PCS/箱
重量	0.43kg/PC; 9.4kg±5%/箱

包装样式图



内包装盒



整箱包装

运输和贮存

1. 运输

产品适用车、船、飞机交通运输工具运输。

在运输中，应使用遮蓬进行防雨和防晒，并保持文明装卸，不应有剧烈振动、撞击等。

2. 贮存

贮存符合I类环境的规定。贮存期限超过6个月的产品建议重新检验，合格后方可使用。

常见问题

1. 设备添加失败怎么办?
 - 1.1 确保设备正常通电，并且处于激活状态；
 - 1.2 需要添加的设备未被其他账号添加过，如被添加过，请手动恢复出厂；
 - 1.3 确保手机与设备两者尽量靠近，建议不超过20米；
 - 1.4 如设备已被强制删除，请手动恢复出厂，然后重新添加设备。
2. 设备离线怎么办?
 - 2.1 请检查设备是否正常通电；
 - 2.2 请检查路由器是否工作正常，网络畅通；
 - 2.3 如使用远程控制，请检查手机网络是否工作正常，网络畅通。
3. 如何远程控制/云场景设置?
如需远程控制/添加云场景设置，需搭配本司超级面板方可使用。
4. 如何共享设备?
请在“我的” — “家庭管理”，进入需要共享的家庭，点击“添加成员”，请按提示将需要设备共享的家人/朋友加入该家庭即完成共享。

注意事项

- 请由具有专业资格的人员进行调试安装；
 - 雷特产品(专有型号除外)不能防水,需避免日晒雨淋,如安装在户外,请用防水箱；
 - 良好的散热条件会延长产品的使用寿命,请把产品安装在通风良好的环境；
 - 请检查使用的工作电压是否符合产品的参数要求；
 - 使用的电线直径大小必须能足够负载连接的LED灯具,并确保接线牢固；
 - 通电调试前,应确保所有接线正确,以避免因接线错误而导致灯具损坏；
 - 如果发生故障,请勿私自维修;如果有疑问,请联系供应商。
- * 本说明书的内容如有变更,恕不另行通知。若内容与您使用的功能有所不同,则以实物为准。如有疑问,欢迎向我司授权的经销商咨询。

保修条例

- 自出厂之日起保修服务期为5年。
- 在保修服务期内出现产品质量问题雷特将给予免费修理或更换服务。

非保修条例:

- 属下列情况不在免费保修或更换服务范围之内:
- 已经超出保修服务期；
 - 过高电压、超负载、操作不当等人为造成的损坏；
 - 产品外形严重损坏或变形；
 - 自然灾害以及人力不可抗拒原因造成的损坏；
 - 产品保修标签和产品唯一条形码损坏；
 - 无雷特签订的合同或发票凭证。
1. 修理或更换是雷特对客户的唯一补救措施。雷特不承担任何附带引起的损害赔偿责任,除非在适用法律范围之内。
2. 雷特享有修正或调整本保修条款的权利,并以书面形式发布为准。

更新日志

版本	更改日期	更改内容	更改人
A0	2021.04.09	正稿	刘伟丽
A1	2021.06.05	更新TUV认证图标	刘伟丽
A2	2021.12.10	更新产品丝印	刘伟丽
A3	2023.03.15	将保修期修改为5年	刘伟丽